



100 Ton MG



350 Ton GG

G Series DP Elevators

Texas International Mfg



150 Ton RG



250 Ton MGG

Features & Applications

Texas International offers "G" series type center latch taper elevators for handling 18° external upset drill pipe and should only be used with this type of pipe. The load ranges from 100 ton to 350 ton.

The elevator is designed with two (2) halves of similar weights for good balance and easier opening and closing. The elevators are equipped with a latch and latch lock combination. A guarded operating latch and an extra handle at the rear of the elevator allow for easier, safer operation. The latch and latch lock secures automatically when the elevator is closed around the pipe.

PRODUCT DESCRIPTION

Size Range:

MG: 2-3/8" - 3-1/2"

RG: 2-3/8" - 5-1/2"

MGG: 3-1/2" - 5-1/2"

GG: 4-1/2" - 5-1/2"

Size Range	Part Number	Model	Load Rating
2-3/8" - 3-1/2"	T30157-XXX	MG	100 Tons
2-3/8" - 3-1/2"	T30156-XXX	RG	150 Tons
4" - 5-1/2"	T23540-XX	RG	150 Tons
3-1/2" - 5-1/2"	T35005-XXX	MGG	250 Tons
4-1/2" - 5-1/2"	T31068-XXX	GG	350 Tons



We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.

Call now for a quote: 281-447- 3980