



**DUETZ 6 Cylinder Diesel, Air Start - Tier 3 (Export)**

**Skid Mounted Hydraulic Power Unit  
Texas International Mfg**

**Features & Applications**



*Deutz 6 cylinder, Diesel powered with Air Start, skid mounted hydraulic power unit.*

- Hydraulic Output: 65 gpm
- Pump Options: Dual Stage
- Murphy Controller
- Hydraulic Cooler
- 100' of 1" & 1.25" Hydraulic Hoses

**Specifications**

**Part No:** TEXP914L06-AIR

**Weight:** 4,200 lbs.

**Length:** 98"

**Width:** 52"

**Height:** 63"

Item	Power (hp)	Speed (rpm)	Torque (ft/lbs)	Oil/filter change (hrs)	Fuel consumption
Deutz Air Cooled Diesel Engine*	113	2300	255	500**	6 gph***
	85	1500	295		

Tanks	Features	Volume (gal)	Working (gal)	Recommended Operating Temp (°F)
Hydraulic	Sight and temperature gauges	180	118	100 - 130
	Filtered breather			
	Top access hatch			
	Fully welded steel construction			
Diesel	Top access filler	57	55	N/A
	Fully welded steel construction			
	Sight and temperature gauges			
	Filtered breather			



**We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.**

**Call now for a quote: 281-447- 3980**