



Starr 13-5/8" Power Tong

Starr Power Tongs

Features & Applications



TORQUE - Rineer 15IN³

TORQUE - Rineer 23IN³

Press.	Speed 1	Speed 2	Speed 3	Speed 4	Press.	Speed 1	Speed 2	Speed 3	Speed 4
PSI	ft.-lb.	ft.-lb.	ft.-lb.	ft.-lb.	PSI	ft.-lb.	ft.-lb.	ft.-lb.	ft.-lb.
2000	24,118	4,824	12,059	2,412	2000	36,981	7,396	18,491	3,698
2250	27,133	5,427	13,566	2,713	2250	-	8,321	20,802	4,160
2500	30,148	6,030	15,074	3,015	2500	-	9,245	23,113	4,623
2750	33,162	6,632	16,581	3,316	2750	-	10,170	25,425	5,085
3000	36,177	7,235	18,089	3,618	3000	-	11,094	27,736	5,547

RPM 2-Speed 15IN³ Motor

RPM 2-Speed 23IN³ Motor

GPM	Speed 1	Speed 2	Speed 3	Speed 4	GPM	Speed 1	Speed 2	Speed 3	Speed 4
10	1.6	8	3.2	16	10	1.0	5.2	2.1	10.4
20	3.2	16	6.4	32	20	2.1	10.4	4.2	20.9
40	6.4	32	12.8	64	40	4.2	20.9	8.3	41.7
60	9.6	48	19.2	96	60	6.3	31.3	12.5	62.6

PRODUCT DESCRIPTION

Part No: Varies

Size Range: 5-1/2" - 13-5/8"

Weight:
with b/u: 3,150 lbs. (1,432 kg)
w/o b/u: 1,675 lbs. (761 kg)

	13 5/8" Tong	13 5/8" Tong w/ Backup
Capacity	5 1/2" - 13 5/8"	5 1/2" - 14 5/8"
Width	43" (109.2 cm)	46" (116.8 cm)
Length	57.6" (146.3 cm)	61.6" (156.5 cm)
Height	47.5" (120.6 cm)	76.4" (190 cm)
Weight	1,675lb (761kg)	3,150lb (1,432kg)
Rated Pressure	3,000 psi; 2,250 psi; 2,000 psi	
Rated Torque	35,000 ft.-lb. (47,453 nm)	
Handle Length	36" (91.4 cm)	

BACKUP JAWS AVAILABLE: 5 1/2" - 14 5/8"
(Other sizes available upon request)



We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.

Call now for a quote: **281-447-3980**