



Starr 14" 50K
Starr 14" 75K

Starr Power Tongs

Features & Applications



	14" Tong	w/ Backup
Capacity	6 5/8"-14"	5 1/2"-15"
Width	41.5" (105.4 cm)	46" (116.8 cm)
Length	65.3" (165.9 cm)	65.3" (165.9 cm)
Height	46.9" (119.1 cm)	80.1" (203.5 cm)
Weight	2,250lb. (1023kg)	3,850lb. (1,750kg)
Rated Pressure	2500 psi	
Rated Torque	75,000 ft-lbs.	
Handle Length	36" (91.4 cm)	

TORQUE - Rineer 23IN ³ 75K Tong					RPM - Rineer 23IN ³ 75K Tong				
Press.	Speed 1	Speed 2	Speed 3	Speed 4	GPM	Speed 1	Speed 2	Speed 3	Speed 4
PSI	ft-lb.	ft-lb.	ft-lb.	ft-lb.					
2000	61,008	10,761	30,504	5,380	10	0.7	3.8	1.4	7.7
2250	68,634	12,106	34,317	6,053	20	1.4	7.7	2.7	15.4
2500	76,260	13,451	38,130	6,726	40	2.7	15.4	5.4	30.7
2750	83,886	14,796	41,943	7,398	60	4.1	23	8.1	46.1
3000	91,512	16,141	45,756	8,071	NOTE - 2 Options Available				
					14" 75 - (1 Handle - 2 Capped Valves)				
					14" 75-BR (Ready to Receive Backup)				

PRODUCT DESCRIPTION

Part No: Varies

Size Range: 6-5/8" - 14"

Weight:
w/o b/u: 2,250 lbs. (1,023 kg)
with b/u: 3,850 lbs. (1,750 kg)

	Motor Shift	Tong Transmission Shift
Speed 1	Low Gear	Low Gear
Speed 2	Low Gear	High Gear
Speed 3	High Gear	Low Gear
Speed 4	High Gear	High Gear

BACKUP JAWS AVAILABLE: 5-1/2" - 15"
(Other sizes available upon request)



We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.

Call now for a quote: 281-447- 3980