




Starr 5-1/2" Power Tong

Starr Power Tongs

Features & Applications



| | Motor Shift | Tong Transmission Shift |
|---------|-------------|-------------------------|
| Speed 1 | Low Gear | Low Gear |
| Speed 2 | Low Gear | High Gear |

| TORQUE Rineer 15IN ³ Motor | | | |
|--|---------|---------|--|
| Press. | Speed 1 | Speed 2 | |
| PSI | ft-lb | ft-lb | |
| 1000 | 8,732 | 1,746 | |
| 2000 | 17,463 | 3,493 | |
| 2250 | 19,646 | 3,929 | |
| 2500 | 21,829 | 4,366 | |
| 2750 | 24,012 | 4,802 | |
| 3000 | 26,195 | 5,239 | |

| GPM | Speed 1 | Speed 2 |
|-----|---------|---------|
| 10 | 2.3 | 11.6 |
| 20 | 4.6 | 23.2 |
| 40 | 9.3 | 46.5 |
| 60 | 13.9 | 69.7 |

BACKUP JAWS AVAILABLE: 2 3/8" – 6 1/4" (Other sizes available upon request)



Weight:



PRODUCT DESCRIPTION

Size Range: 2-3/8" - 5-1/2"

with b/u: 2,400 lbs. (1,090 kg) w/o b/u: 1,350 lbs. (613 kg)

Part No: Varies



We Stock TI Manufactured handling tools backed by Expertise, MPI and In-House Load Test Certification.

Call now for a quote: 281-447-3980

